WHAT IS CLAIMED IS:

1. A method of making a polymer nanocomposite comprising:

combining a polymer dispersion with a clay mineral dispersion to form a claypolymer dispersion;

adding a flocculating agent to the clay-polymer dispersion mixture to form the polymer nanocomposite.

- 2. The method of claim 1, further comprising forming a polymer dispersion by adding a polymer to a liquid carrier.
- 3. The method of claim 1, further comprising forming a clay mineral dispersion by adding a clay mineral to a liquid carrier.
- 4. The method of claim 1, wherein the polymer dispersion comprises a latex.
- 5. The method of claim 1, wherein the polymer dispersion comprises a styrene-butadiene.
- 6. The method of claim 1 wherein the polymer dispersion comprises a polyurethane dispersion.
- 7. The method of claim 1 wherein the polymer dispersion comprises polyvinyl chloride, an acrylic rubber, a butyl-containing polymer, a chlorosulfonated polyethylene rubber, a fluoroelastomer, or a polyisoprene.
- 8. The method of claim 1 wherein the polymer dispersion comprises a negatively charged polymer and wherein the flocculating agent comprises a positively


Atty. Dkt. No. 5628-13301

10 ⊫≟

-A

ر 15

10 mg



- 9. The method of claim 1 wherein the polymer dispersion comprises a positively charged polymer and wherein the flocculating agent comprises a negatively charged compound.
- 10. The method of claim 1, wherein the polymer dispersion comprises a polymer and a surfactant dispersed in a liquid carrier.
- 11. The method of claim 1, wherein the polymer dispersion comprises up to about 80% by weight of the polymer.
- 12. The method of claim 1, further comprising forming the polymer dispersion by subjecting a mixture of the polymer in the first liquid carrier to a shearing process.
- 13. The method of claim 1, wherein the clay mineral dispersion comprises montmorillonite.
- 14. The method of claim 1, wherein the clay mineral dispersion comprises bentonite.
- 15. The method of claim 1, wherein the clay mineral dispersion comprises hectorite, saponite, attapulgite, beidelite, stevensite, sauconite, nontronite, Laponite, or sepiolite.
- The method of claim 1, wherein the clay mineral dispersion comprises hydrotalcite.
 - 17. The method of claim 1, wherein the clay mineral dispersion comprises between about 1 to about 10% by weight of the clay mineral.

5

10

`` ``#_#

VIII TO THE TOTAL THE TOTAL TO

- 18. The method of claim 1, further comprising forming the clay dispersion by subjecting a mixture of the clay mineral in the second liquid carrier to a high shear process.
- The method of claim 1, wherein the clay-polymer dispersion comprises up to about 90% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
 - 20. The method of claim 1, wherein the clay-polymer dispersion comprises up to about 30% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
 - 21. The method of claim 1, wherein the clay-polymer dispersion comprises up to about 10% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
 - 22. The method of claim 1 wherein the flocculating agent comprises an organic salt.
 - 23. The method of claim 1 wherein the flocculating agent comprises a quaternary ammonium compound.
 - 24. The method of claim 1 wherein the flocculating agent comprises a quaternary ammonium compound having the structure:

$$R_1$$
 $| +$
 R_2 — N — R_4 $X^ | R_3$

wherein R₁, R₂, R₃, and R₄ are independently alkyl groups, aryl groups or arylalkyl groups, and wherein at least one of R₁, R₂, R₃, or R₄ is an aliphatic group

20

25

30

- derived from a naturally occurring oil.
- 25. The method of claim 1 wherein the flocculating agent comprises an inorganic salt.
- 5 26. The method of claim 1 wherein the flocculating agent comprises a Group I metal salt.
 - 27. The method of claim 1 wherein the flocculating agent comprises a Group II metal salt.
 - 28. The method of claim 1 wherein the flocculating agent comprises a mineral compound.
 - 29. The method of claim 1, wherein the flocculating agent comprises between about 1% to about 10% by weight of the clay-polymer dispersion.
 - 30. A polymer nanocomposite prepared by the method comprising:

beognaphy)

combining a polymer dispersion with a clay mineral dispersion to form a claypolymer dispersion;

adding a flocculating agent to the clay-polymer dispersion mixture to form the polymer nanocomposite.

- The polymer nanocomposite of claim 30, wherein the method further comprises forming a polymer dispersion by adding a polymer to a liquid carrier.
 - 32. The polymer nanocomposite of claim 30, wherein the method further comprises forming a clay mineral dispersion by adding a clay mineral to a liquid carrier.

30

10

μå

*.] |-|15

Ħ.

20

- 34. The polymer nanocomposite of claim 30, wherein the polymer dispersion comprises a styrene-butadiene.
- 35. The polymer nanocomposite of claim 30, wherein the polymer dispersion comprises a polyurethane dispersion.
- 36. The polymer nanocomposite of claim 30, wherein the polymer dispersion comprises polyvinyl chloride, an acrylic rubber, a butyl-containing polymer, a chlorosulfonated polyethylene rubber, a fluoroelastomer, or a polyisoprene.
- 37. The polymer nanocomposite of claim 30, wherein the polymer dispersion comprises a negatively charged polymer and wherein the flocculating agent comprises a positively charged compound.
- 38. The polymer nanocomposite of claim 30 wherein the polymer dispersion comprises a positively charged polymer and wherein the flocculating agent comprises a negatively charged compound.
- 39. The polymer nanocomposite of claim 30, wherein the polymer dispersion comprises a polymer and a surfactant dispersed in a liquid carrier.
- 25 40. The polymer nanocomposite of claim 30, wherein the polymer dispersion comprises up to about 80% by weight of the polymer.
 - 41. The polymer nanocomposite of claim 30, wherein the method further comprises forming the polymer dispersion by subjecting a mixture of the polymer in the first liquid carrier to a shearing process.

30

- 42. The polymer nanocomposite of claim 30, wherein the clay mineral comprises montmorillonite.
- 5 43. The polymer nanocomposite of claim 30, wherein the clay mineral comprises bentonite.
 - 44. The polymer nanocomposite of claim 30, wherein the clay mineral comprises hectorite, saponite, attapulgite, beidelite, stevensite, sauconite, nontronite, Laponite or sepiolite.
 - 45. The polymer nanocomposite of claim 30, wherein the clay mineral comprises hydrotalcite.
 - 46. The polymer nanocomposite of claim 30, wherein the clay mineral dispersion comprises between about 1 to about 10% by weight of the clay mineral.
 - 47. The polymer nanocomposite of claim 30, wherein the method further comprises forming the clay dispersion by subjecting a mixture of the clay mineral in the second liquid carrier to a high shear process.
 - 48. The polymer nanocomposite of claim 30, wherein the clay-polymer dispersion comprises up to about 90% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
 - 49. The polymer nanocomposite of claim 30, wherein the clay-polymer dispersion comprises up to about 30% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
- The polymer nanocomposite of claim 30, wherein the clay-polymer dispersion

Atty. Dkt. No. 5628-13301

comprises up to about 10% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.

5

52.

51. The polymer nanocomposite of claim 30, wherein the flocculating agent comprises an organic salt.

The polymer nanocomposite of claim 30, wherein the flocculating agent

10

||-i= 15 إ

53. The polymer nanocomposite of claim 30, wherein the flocculating agent

comprises a quaternary ammonium compound having the structure:

 $-R_4$

comprises a quaternary ammonium compound.

wherein R_1 , R_2 , R_3 , and R_4 are independently alkyl groups, aryl groups or arylalkyl groups, and wherein at least one of R₁, R₂, R₃, or R₄ is an aliphatic group derived from a naturally occurring oil.

- 25
- 54. The polymer nanocomposite of claim 30, wherein the flocculating agent comprises an inorganic salt.
- 55. The polymer nanocomposite of claim 30, wherein the flocculating agent comprises a Group I metal salt.
- 30

56.

comprises a Group II metal salt.

The polymer nanocomposite of claim 30, wherein the flocculating agent

57. The polymer nanocomposite of claim 30, wherein the flocculating agent

- 5
- 58. The polymer nanocomposite of claim 30, wherein the flocculating agent comprises between about 1% to about 10% by weight of the clay-polymer dispersion.
- 10
- 15 IJ


A method of making a polymer nanocomposite comprising: 59.

> forming a clay mineral dispersion by adding a clay mineral and an onium compound to a liquid carrier, wherein the onium compound is present in excess of the cation exchange capacity of the clay mineral such that a portion of the onium compound present is not bound to the clay mineral;

combining a polymer dispersion with the clay mineral dispersion to form the polymer nanocomposite.

- The method of claim 59, wherein the onium compound comprises a quaternary mmonium compound.
- 61. The method of claim 59 wherein the onium compound comprises a quaternary 20 ammonium compound having the structure:

30



wherein R₁, R₂, R₃, and R₄ are independently alkyl groups, aryl groups or arylalkyl groups, and wherein at least one of R₁, R₂, R₃, or R₄ is an aliphatic group derived from a naturally occurring oil.


- 62. The method of claim 59, wherein the amount of onium compound is up to about 3 times the cation exchange capacity of the clay mineral.
- 63. The method of claim 59, further comprising forming a polymer dispersion by adding a polymer to a liquid carrier.
- 64. The method of claim 59, wherein the polymer dispersion comprises a latex.
- 65. The method of claim 59, wherein the polymer dispersion comprises a styrene-butadiene.
- 66. The method of claim 59 wherein the polymer dispersion comprises a polyurethane dispersion.
- 67. The method of claim 59 wherein the polymer dispersion comprises polyvinyl chloride, an acrylic rubber, a butyl-containing polymer, a chlorosulfonated polyethylene rubber, a fluoroelastomer, or a polyisoprene.
- 68. The method of claim 59, wherein the polymer dispersion comprises a polymer and a surfactant dispersed in a liquid carrier.
- 69. The method of claim 59, wherein the polymer dispersion comprises up to about 80% by weight of the polymer.
- The method of claim 59, further comprising forming the polymer dispersion by subjecting a mixture of the polymer in the first liquid carrier to a shearing process.
 - 71. The method of claim 59, wherein the clay mineral comprises montmorillonite.
- The method of claim 59, wherein the clay mineral comprises bentonite.

- 73. The method of claim 59, wherein the clay mineral comprises hectorite, saponite, attapulgite, beidelite, stevensite, sauconite, nontronite, Laponite, or sepiolite.
- 5 74. The method of claim 59, wherein the mineral clay comprises hydrotalcite.
 - 75. The method of claim 59, wherein the clay mineral dispersion comprises between about 1 to about 10% by weight of the clay mineral.
 - 76. The method of claim 59, wherein forming a clay dispersion comprises subjecting a mixture of the clay mineral in the liquid carrier to a high shear process.
 - 77. The method of claim 59, wherein the clay-polymer dispersion comprises up to about 90% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
 - 78. The method of claim 59, wherein the clay-polymer dispersion comprises up to about 30% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
 - 79. The method of claim 59, wherein the clay polymer dispersion comprises up to about 10% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
- 80. A polymer nanocomposite prepared by the method comprising:

forming a clay mineral dispersion by adding a clay mineral and an onium compound to a liquid carrier, wherein the onium compound is present in excess of the cation exchange capacity of the clay mineral such that a portion of the onium compound present is not bound to the clay mineral;

combining the polymer dispersion with the clay mineral dispersion to form the polymer nanocomposite.

- The polymer nanocomposite of claim 80, wherein the onium compound comprises a quaternary ammonium compound.
 - 82. The polymer nanocomposite of claim 80, wherein the onium compound comprises a quaternary ammonium compound having the structure:



wherein R_1 , R_2 , R_3 , and R_4 are independently alkyl groups, aryl groups or arylalkyl groups, and wherein at least one of R_1 , R_2 , R_3 , or R_4 is an aliphatic group derived from a naturally occurring oil.

- 83. The polymer nanocomposite of claim 80, wherein the amount of onium compound is up to about 3 times the cation exchange capacity of the clay mineral.
- 84. The polymer nanocomposite of claim 80, wherein the method further comprises forming a polymer dispersion by adding a polymer to a liquid carrier.
 - 85. The polymer nanocomposite of claim 80, wherein the polymer dispersion comprises a latex.
- 30 86. The polymer nanocomposite of claim 80, wherein the polymer dispersion comprises a styrene-butadiene.

- The polymer nanocomposite of claim 80, wherein the polymer dispersion comprises a polyurethane dispersion.
- 88. The polymer nanocomposite of claim 80, wherein the polymer dispersion comprises polyvinyl chloride, an acrylic rubber, a butyl-containing polymer, a chlorosulfonated polyethylene rubber, a fluoroelastomer, or a polyisoprene.
- 89. The polymer nanocomposite of claim 80, wherein the polymer dispersion comprises a polymer and a surfactant dispersed in a liquid carrier.
- 90. The polymer nanocomposite of claim 80, wherein the polymer dispersion comprises up to about 80% by weight of the polymer.
- 91. The polymer nanocomposite of claim 80, wherein the method further comprises forming the polymer dispersion by subjecting a mixture of the polymer in a liquid carrier to a shearing process.
- 92. The polymer nanocomposite of claim 80, wherein the clay mineral comprises montmorillonite.
- 93. The polymer nanocomposite of claim 80, wherein the clay mineral comprises bentonite.
- 94. The polymer nanocomposite of claim 80, wherein the clay mineral comprises hectorite, saponite, attapulgite, beidelite, stevensite, sauconite, nontronite, Laponite, or sepiolite.
- 95. The polymer nanocompite of claim 80, wherein the clay mineral comprises hydrotalcite.

25

5

10

e L

'n,

IJ

20

- The polymer nanocomposite of claim 80, wherein the clay mineral dispersion comprises between about 1 to about 10% by weight of the clay mineral.
- 97. The polymer nanocomposite of claim 80, wherein the method further comprises forming a clay dispersion by subjecting a mixture of the clay mineral in the second liquid carrier to a high shear process.
- 98. The polymer nanocomposite of claim 80, wherein the clay-polymer dispersion comprises up to about 90% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
- 99. The polymer nanocomposite of claim 80, wherein the clay-polymer dispersion comprises up to about 30% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.
- 100. The polymer nanocomposite of claim 80, wherein the clay-polymer dispersion comprises up to about 10% by weight of clay mineral with respect to the weight of polymer in the clay-polymer dispersion.